

Clamp meter

testo 770-1
testo 770-2
testo 770-3

Unique grab mechanism makes it easier to work at tight measuring points


Auto AC/DC for current and voltage

Large two-line display

True root mean square measurement - TRMS

With additional functions, such as starting current, power and μA measurement

Bluetooth and testo Smart App



 **Bluetooth®**
+ App

testo Smart App
for free download



The three instruments in the testo 770 clamp meter family are ideally suited for current measurement in switching cabinets. One of the two pincer arms can be fully retracted into the instrument. This unique grab mechanism means that cables in tight switching cabinets can be easily grabbed. The automatic measurement parameter detection also ensures reliable work: in the current and voltage area, all three instruments detect direct and alternating current and select other parameters such as resistance, continuity, diode and capacitance automatically.

The testo 770-1 model is the standard version for daily measuring tasks, including starting current measurement. In addition, the testo 770-2 contains both a μA area as well as a temperature measurement by means of an optional thermocouple adapter type K. The testo 770-3 also calculates all output ratings, has a Bluetooth interface and the possibility of connecting to the testo Smart App to show the measuring profile as a graph or to document it directly in a report.

Technical data/accessories

testo 770-1

testo 770-1, TRMS clamp meter, including batteries and 1 set of measuring cables

Order no. 0590 7701



testo 770-2

testo 770-2, TRMS clamp meter, including batteries, 1 set of measuring cables and 1 x adapter for type K thermocouples

Order no. 0590 7702



testo 770-3


testo 770-3, TRMS clamp meter, including batteries and 1 set of measuring cables

Order no. 0590 7703



| Accessories | Order no. |
|---|-----------|
| Type K thermocouple adapter (for testo 770-2/-3 only) | 0590 0021 |
| Set of safety crocodile clips, suitable for 0590 0011 and 0590 0012 | 0590 0008 |
| Set of crocodile clips, suitable for 0590 0010 | 0590 0009 |
| Set of 2 mm measuring cables (angled plug), suitable for 0590 0009 | 0590 0010 |
| Set of 4 mm standard measuring cables (angled plug), suitable for 0590 0008 | 0590 0011 |
| Set of 4 mm standard measuring cables (straight plug), suitable for 0590 0008 | 0590 0012 |
| Set of measuring cable extensions (straight plug) | 0590 0013 |
| Set of measuring cable extensions (angled plug) | 0590 0014 |
| testo 755 / testo 770 transport bag | 0590 0017 |
| ISO calibration certificate clamp meter | 0520 0770 |
| DAkkS calibration clamp meter | 0520 0771 |

| Technical data | testo 770-1 | testo 770-2 | testo 770-3 |
|-------------------------------|---|---------------------|-----------------------|
| True RMS | ✓ | | |
| Basic accuracy | 0.8 % | | 0.1 % |
| Voltage measuring range | 1 mV to 600 V AC/DC | | |
| Current measuring range | 0.1 to 400 A AC/DC | | 0.1 to 600 A AC/DC |
| Power measurement | – | | ✓ |
| µA measuring range | – | 0.1 to 400 µA AC/DC | |
| Resistance measuring range | 0.1 Ω to 40 MΩ | | 0.1 Ω to 60 MΩ |
| Frequency measuring range | 0.001 Hz to 10 kHz | | |
| Capacitance measuring range | 0.001 µF to 100 µF | | 0.001 µF to 60,000 µF |
| Temperature measuring range | – | -20 to +500 °C | |
| Bluetooth and testo Smart App | – | | ✓ |
| Continuity testing | ✓ | | |
| Diode test | ✓ | | |
| Display (counts) | 4,000 | | 6,000 |
| Measurement category | CAT IV 600 V CAT III 1,000 V | | |
| Compatibility | requires iOS 11.0 or newer / Android 6.0 or newer | | |
| | requires mobile terminal device with Bluetooth® 4.0 | | |
| Operating temperature | -10 to +50 °C | | |
| Storage temperature | -15 to +60 °C | | |
| Dimensions | 243 x 96 x 43 mm (L x W x H) | | |
| Weight | 378 g | | |
| Authorizations | CSA, CE | | |
| Standards | EN 61326-1, EN 61140 | | |



testo Smart App

The App turns your smartphone/tablet into the display for the testo 770. Both the operation of the measuring instrument and the display of the readings are achieved by Bluetooth® via the testo Smart App on your smartphone or tablet – irrespective of the measuring location. In addition, you can use the App to create measurement reports, add photos and comments to these and send them by e-mail. For iOS and Android.